



Cesto tondo fisso  
Round fixed basket  
Panier rond fixe  
Fest Rundkorb  
Cesta redonda fija



A = Caricamento acqua / Chargement eau / Water inlet  
Wassereintritt / Carga agua: 3/4 "

B = Allacciamento elettrico / Branchement électrique  
Electric connection / Elektrischer Anschluss / Conexión electrica

C = Scarico / Vidange / Drain / Abfluss / Desagüe: 1 "

## OPTIONAL



- Pannello inferiore in acciaio inox
- Stainless steel bottom panel
- Panneau socle en acier inox
- Edelstahl unter Teil
- Panel inferior en acero inox

 /h 1000 ÷ 1200

 1x230 V  
50 Hz

 410 mm Ø

## OPTIONAL

DD



- Dosatore Detersivo Peristaltico regolabile
- Adjustable Peristaltic Soap Pump
- Doseur de produit de lavage
- Spülmitteldosierer, regulierbar
- Dosificador de detergente regulable

PS



- Pompa di scarico
- Drain pump
- Pompe de vidange
- Ablaufpumpe
- Bomba de desagüe

## CARATTERISTICHE TECNICHE - TECHNICAL DATA - CARACTERISTIQUES TECHNIQUES - TECHNISCHE EIGENSCHAFTEN - CARACTERÍSTICAS TÉCNICAS

Alimentazione elettrica Electric supply <i>Alimentation électrique</i> Betriebsspannung <i>Alimentación eléctrica</i>	<b>1x230 V/50Hz</b>	Capacità vasca Wash tank capacity <i>Capacité cuve</i> Wanneninhalt <i>Capacidad cuba</i>	<b>lt. 14</b>	Pressione alimentazione Required water pressure Pression alimentation Wasserzulaufdruck Presión alimentación	<b>bar 2 ÷ 4</b>
Potenza pompa lavaggio Wash pump power <i>Puissance pompe de lavage</i> Pumpenleistung <i>Potencia bomba lavado</i>	<b>Kw 0,45 (HP 0,60)</b>	Capacità boiler Boiler capacity <i>Capacité surchauffeur</i> Boilerinhalt <i>Capacidad boiler</i>	<b>lt. 5,5</b>	Ø tubo di carico/scarico Water supply hose/drain hose Diamètre tuyau d'entrée/de vidange Einfühschlauch/Abflaufschlauch Ø tubo de carga/de desagüe	<b>3/4" / 25</b>
Resistenza boiler Boiler element <i>Puissance résistance surchauffeur</i> Heizleistung Boiler <i>Potencia resistencia boiler</i>	<b>W 2700</b>	Temperatura lavaggio/risciacquo Wash-rinse temperature <i>Température lavage-rinçage</i> Spül-Nachspültemperatur <i>Temperatura lavado-aclarado</i>	<b>55° / 85°</b>	Acqua alimentazione Supply water Eau d'alimentation Anschlussstemp Agua de alimentación	<b>Max 50°C</b>
Resistenza vasca Tank element <i>Puissance résistance cuve</i> Heizleistung Wanne <i>Potencia resistencia cuba</i>	<b>W 1800</b>	Durata ciclo Cycle time <i>Durée du cycle</i> Spülzyklusdauer <i>Duración ciclo</i>	<b>120 sec.</b>	Livello rumorosità Noise emission <i>Émission sonore</i> Arbeitsplatzbezogener emissionswert <i>Emisión de ruidos</i>	<b>&lt; 60 dBA</b>
Potenza massima assorbita Total power rating <i>Puissance maximale</i> Max Stromaufnahme <i>Potencia máxima</i>	<b>W 3150</b>	Cicli ora Cycles/hour up to Cycles par heure Körbe pro Stunde Ciclos/h	<b>30</b>	Peso netto Net Weight <i>Poids net</i> Netto Gewicht Peso neto	<b>Kg 36</b>