

LAVABICCHIERI • GLASSWASHERS • LAVE-VERRES • GLÄSERSPÜLMASCHINEN
mod. E40

| cod. OWB2QACSM0001E05

DOTAZIONI • EQUIPMENT • ÉQUIPEMENT • AUSRÜSTUNG

Dosatore meccanico del brillantante
 Mechanical rinse aid dispenser
 Doseur mécanique de produit de rinçage
 Mechanischer Klarspülerspender



Due cesti stoviglie
 Two crockery baskets
 Deux paniers à vaisselle
 Zwei Geschirrkörbe



400 x 400 mm


CARATTERISTICHE TECNICHE • TECHNICAL FEATURES • CARACTÉRISTIQUES TECHNIQUES • TECHNISCHE DATEN

Alimentazione elettrica Electric supply Alimentation électrique Stromversorgung	230 V (50 Hz)	Capacità boiler Boiler capacity Capacité surchauffeur Kesselkapazität	5 L	Pressione alimentazione Required water pressure Pression alimentation Wasserzulaufdruck	2 ÷ 4 bar
Potenza pompa lavaggio Wash pump power Puissance pompe de lavage Pumpenleistung	0,18 kW	Capacità vasca Wash tank capacity Capacité cuve Wanneninhalt	14 L	Tubo di carico/scarico Ø Water supply hose/drain hose Tuyau d'entrée/de vidange Einfüllschlauch/Ablaufschlauch	3/4" gas/25 mm
Resistenza boiler Boiler element Puissance résistance surchauffeur Heizleistung Boiler	2,7 kW	Temperatura risciacquo Rinse temperature Température rinçage Spültemperatur	82 °C	Temperatura acqua alimentazione Supply water temperature Température de l'eau d'alimentation Speisewassertemp	MAX 50 °C
Resistenza vasca Tank element Puissance résistance cuve Heizleistung Wanne	1,8 kW	Temperatura lavaggio Wash temperature Température lavage Waschtemperatur	55 °C	Livello di rumorosità Noise emission Émission sonore Arbeitsplatzbezogener emissionswert	<75 dBA
Potenza massima assorbita Total power rating Puissance maximale Maximale aufgenommene Leistung	3 kW	Durata ciclo Cycle time Durée du cycle Zykluslänge	120"	Peso netto Net weight Poids net Nettogewicht	36 kg


OPTIONAL • OPTIONAL • OPTIONNEL • OPTIONAL



Dosatore peristaltico detergente e brillantante
Peristaltic detergent and rinse aid dispenser
Doseur péristaltique de produit de lavage et de rinçage
Peristaltischer Dosierer für Spülmittel und Klarspüler



Pompa di scarico
Drain pump
Pompe de vidange
Ablaufpumpe



Filtro di superficie in polipropilene
Surface filter in polypropylene
Filtre de surface en polypropylène
Oberflächenfilter aus Polypropylen



Cesto rotondo Ø41 cm
Round basket Ø41 cm
Panier rond Ø41 cm
Rundkorb Ø41 cm

ACCESSORI • ACCESSORIES • ACCESSOIRES • ZUBEHÖR



Addolcitore automatico
Automatic water softener
Adoucisseur automatique
Automatischer Wasserenthärter




Supporto lavastoviglie
Dishwasher support
Support lave-vaisselle
Geschirrspüler-Support



Addolcitore manuale
Manual water softener
Adoucisseurs manuels
Manuelle Wasserenthärter

DISEGNO TECNICO • TECHNICAL DRAWING • DESSIN TECHNIQUE • TECHNISCHE ZEICHNUNG



A

Morsetto equipotenziale
Clamp equipotential
Serrer équipotentiel
Klemme Äquipotential

D

Scarico acqua
Drain water
Drain d'eau
Wasserabfluss

B

Ingresso acqua
Water inlet
Arrivée d'eau
Wassereinlass

E

Tubi detergenti
Detergent pipes
Tubes de détergent
Waschmittelröhrchen

C

Alimentazione elettrica
Power supply
Alimentation électrique
Elektrische Energie

F

Griglia di ventilazione
Ventilation grid
Grille de ventilation
Gitter von Belüftung